



Śred. nom. DN	Rura		Kolnierz						Śruby		
	A	B ₁	D	K	d ₁	f ₁	C ₁	L	masa kg	n	gwint
Dla kolnierzy DN 10 do DN 40 obowiązują wymiary jak dla ciśnienia PN 40											
Dla kolnierzy DN 50 do DN 150 obowiązują wymiary jak dla ciśnienia PN 16											
200	219,1	221,5	340	295	268	2	24	22	8,78	8	M20
250	273,0	276,5	395	350	320	2	26	22	11,23	12	M20
300	323,9	327,5	445	400	370	2	26	22	12,93	12	M20
350	355,6	359,5	505	460	430	2	28	22	19,60	16	M20
400	406,4	411	565	515	482	2	32	26	26,57	16	M24
450	457,0	462	615	565	532	2	36	26	32,55	20	M24
500	508,0	513,5	670	620	585	2	38	26	39,06	20	M24
600	610,0	616,5	780	725	685	2	42	30	52,94	20	M27
700	711,0	po uzgodnieniu z zamawiającym	895	840	800	2	po uzgodnieniu z zamawiającym	30	-	24	M27
800	813,0		1015	950	905	2		33	-	24	M30
900	914,0		1115	1050	1005	2		33	-	28	M30
1000	1016,0		1230	1160	1110	2		36	-	28	M33
1200	1219,0		1455	1380	1330	2		39	-	32	M36
1400	1422,0		1675	1590	1535	2		42	-	36	M39
1600	1626,0		1915	1820	1760	2		48	-	40	M45
1800	1829,0		2115	2020	1960	2		48	-	44	M45
2000	2032,0		2325	2230	2170	2		48	-	48	M45

Ciśnienie nominalne PN 16											
Śred. nom. DN	Rura		Kolnierz						Śruby		
	A	B ₁	D	K	d ₁	f ₁	C ₁	L	masa kg	n	gwint
Dla kolnierzy DN 10 do DN 40 obowiązują wymiary jak dla ciśnienia PN 40											
50	57,0*	58	165	125	102	2	19	18	2,45	4	M16
	60,3	61,5							2,40		
65	76,1	77,5	185	145	122	2	20	18	2,95	8	M16
80	88,9	90,5	200	160	138	2	20	18	3,37	8	M16
100	108,0*	109	220	180	158	2	22	18	4,34	8	M16
	114,3	116							4,13		
125	133,0*	135	250	210	188	2	22	18	5,35	8	M16
	139,7	141,5							5,10		
150	159,0*	161	285	240	212	2	24	22	7,21	8	M20
	168,3	170,5							6,74		
200	219,1	221,5	340	295	268	2	26	22	9,26	12	M20
250	273,0	276,5	405	355	320	2	29	26	13,54	12	M24
300	323,9	327,5	460	410	378	2	32	26	18,23	12	M24
350	355,6	359,5	520	470	438	2	35	26	27,28	16	M24
400	406,4	411	580	525	490	2	38	30	34,84	16	M27
450	457,0	462	640	585	550	2	42	30	45,01	20	M27
500	508,0	513,5	715	650	610	2	46	33	62,55	20	M30
600	610,0	616,5	840	770	725	2	52	36	94,11	20	M33
700	711,0	po uzgodnieniu z zamawiającym	910	840	795	2	po uzgodnieniu z zamawiającym	36	-	24	M33
800	813,0		1025	950	900	2		39	-	24	M36
900	914,0		1125	1050	1000	2		39	-	28	M36
1000	1016,0		1255	1170	1115	2		42	-	28	M39
1200	1219,0		1485	1390	1330	2		48	-	32	M45
1400	1422,0		1685	1590	1530	2		48	-	36	M45
1600	1626,0		1930	1820	1750	2		56	-	40	M52
1800	1829,0		2130	2020	1950	2		56	-	44	M52
2000	2032,0		2345	2230	2150	2		62	-	48	M56