



OBEJMY DO RUR TYPU "E"

du mm	d mm	h mm	h1 mm	l mm	d1 mm	d2 mm	Masa kg	g mm
7	5	17	25	12	M5	-	0.014	6-9
9	5	17	27	14	M5	-	0.015	6-9
11	6	18	30	17	M6	-	0.026	6-9
13	6	18	32	19	M6	-	0.027	6-9
15	6	18	33	21	M6	-	0.028	6-9
17	6	18	36	23	M6	-	0.029	6-9
19	6	20	38	25	M6	-	0.03	6-9
21	8	22	43	29	M8	-	0.064	6-9
23	8	22	45	31	M8	-	0.066	6-9
26	8	22	49	34	M8	-	0.069	6-9
28	8	22	51	36	M8	-	0.071	6-9
29	8	22	52	37	M8	-	0.073	6-9
31	8	22	53	39	M8	-	0.074	6-9
33	8	24	56	41	M8	-	0.076	6-9
35	8	24	58	43	M8	-	0.078	6-9
37	8	24	60	45	M8	-	0.08	6-9
40	10	24	68	50	M10	-	0.13	8-11
44	10	24	72	54	M10	-	0.14	8-11
46	10	24	74	56	M10	-	0.15	8-11
48	10	24	70	58	M10	-	0.16	8-11
50	12	45	74	62	M12	12.2	0.23	8-12
52	12	45	76	64	M12	12.2	0.25	8-12
59	12	45	83	71	M12	12.2	0.26	8-12
62	12	45	86	74	M12	12.2	0.30	8-12
67	12	45	91	79	M12	12.2	0.36	8-12
78	16	55	108	94	M16	16.3	0.59	10-14
83	16	55	113	99	M16	16.3	0.62	10-14
86	16	55	116	102	M16	16.3	0.64	10-14
92	16	55	123	108	M16	16.3	0.66	10-14

du mm	d mm	h mm	h1 mm	l mm	d1 mm	d2 mm	Masa kg	g mm
104	16	55	134	120	M16	16.3	0.71	10-14
110	16	55	140	126	M16	16.3	0.73	10-14
118	16	55	148	134	M16	16.3	0.77	10-14
137	20	65	173	157	M20	20.5	1.42	10-15
144	20	65	180	164	M20	20.5	1.47	10-15
163	20	65	195	183	M20	20.5	1.59	10-15
172	20	65	208	192	M20	20.5	1.65	10-15
198	20	65	234	218	M20	20.5	1.81	10-15
223	24	75	267	247	M24	24.5	2.98	12-18
248	24	75	289	272	M24	24.5	3.20	12-18
277	24	75	321	301	M24	24.5	3.48	12-18
303	24	75	344	327	M24	24.5	3.70	12-18
328	24	75	372	352	M24	24.5	3.94	12-18
360	30	95	415	390	M30	30.5	7.00	15-21
411	30	95	465	441	M30	30.5	7.70	15-21
462	30	95	516	492	M30	30.5	8.50	15-21
513	30	95	567	543	M30	30.5	9.20	15-21
615	38	110	678	653	M36	36.5	17.40	15-23
716	38	110	778	754	M36	36.5	19.80	15-23
818	40	120	886	858	M39	39.5	25.00	18-25
920	40	120	986	960	M39	39.5	27.00	18-25
1022	40	120	1086	1062	M39	39.5	30.20	18-25

Długości obejm ustalono dla pówek o grubości "g" podanej w tablicy